

INSULATE
SEAL
PROTECT

3:1
SHRINK RATIO



THIN WALL ADHESIVE LINED CROSS-LINKED POLYOLEFIN

ADHESIVE LINED HEAT SHRINK TUBING WITH ENVIRONMENTAL SEALING CAPABILITY IDEAL FOR A VARIETY OF APPLICATIONS INCLUDING AUTOMOTIVE AND MARINE WIRE HARNESS BUNDLES, INDUSTRIAL SPLICES, BREAKOUTS AND CONNECTOR TO CABLE TRANSITIONS

FEATURES AND BENEFITS


- 3:1 shrink ratio
- Flame retardant
- Superior sealing against water, moisture or other contaminants
- High shrink ratio allows for coverage of irregularly shaped connectors and components
- Inner adhesive bonds to plastics, rubber, neoprene, steel and polyethylene
- Continuous operating temperature: -55°C to 110°C
- Shrink temperature: 120°C

STANDARDS

- Industrial, electronic and automotive OEM approvals


TYPICAL APPLICATIONS

- Environmental sealing and strain relief of connectors and terminals
- Moisture sealing and electrical insulation of simple in-line splices
- Abrasion resistance for tubes and pipes
- Repair of damaged wire harnesses



DIMENSIONS

ORDER NUMBER	EXPANDED		RECOVERED						LENGTHS (STICKS)	
	INTERNAL DIAMETER (MIN.) D		INTERNAL DIAMETER (MAX.) d		TOTAL WALL THICKNESS (NOM.) W		MELTABLE WALL THICKNESS (NOM.)			
	MM	IN	MM	IN	MM	IN	MM	IN	M	IN
0125	3.2	1/8	1.0	0.040	1.0	0.040	0.5	0.020	1.2	48
0187	4.7	3/16	1.5	0.060	1.0	0.040	0.5	0.020	1.2	48
0250	6.4	1/4	2.0	0.080	1.0	0.040	0.5	0.020	1.2	48
0312	7.9	5/16	2.5	0.100	1.3	0.050	0.7	0.027	1.2	48
0375	9.5	3/8	3.2	0.125	1.5	0.060	0.7	0.027	1.2	48
0500	12.7	1/2	4.1	0.160	1.8	0.070	0.8	0.030	1.2	48
0750	19.1	3/4	6.4	0.250	1.8	0.070	0.8	0.030	1.2	48
1000	25.4	1	8.1	0.320	2.5	0.100	1.0	0.040	1.2	48
1250	31.8	1¼	10.6	0.416	2.5	0.100	1.0	0.040	1.2	48
1500	39.9	1½	13.0	0.510	2.5	0.100	1.0	0.040	1.2	48



ORDERING

- Select a dimension which will shrink snugly over the component to be covered. If recovery is restricted the resultant wall thickness will be less than specified.
- Select options:
 - Colour: Black (BK), Red (RD), Clear (CL), Blue (BL), White (WT), Yellow (YW)
 - Length: Standard Stick, Spool or custom length
- Please specify the product name, order reference number and options you require
- Order Example: CPA 100, 0125, black, 48 in lengths

Please contact your Customer Service Representative for information on custom colours, sizes, lengths and material data sheet.

All information contained in this data sheet is believed to be reliable. We advise, however, that customers should separately evaluate the suitability of our products for their particular application. DSG-Canusa and ShawCor give no guarantees in respect of the accuracy or sufficiency of the information presented and disclaim any liability regarding its use. Our responsibilities are only those listed in our Standard Terms and Conditions of Sale for these products. In no instance will we be liable for any eventual, indirect or consequential damage or damages arising from the sale, resale, transfer, use or misuse of the product.